

## Customized CNC Brass Ball Head Bolt Wholesale

<b>Code</b>	1
<b>Discount</b>	Rs 10.00
<b>Expires On</b>	2020-10-05 5:17 AM
<b>External URL</b>	<a href="https://www.yuanzhi-autoparts.com/b/stainless-steel-bolts.html">https://www.yuanzhi-autoparts.com/b/stainless-steel-bolts.html</a>
<b>Keywords</b>	ball head bolt
<b>Hits</b>	726
<b>URL</b>	<a href="https://www.indiabusinessstoday.in/deals/detail/customized-cnc-brass-ball-head-bolt-wholesale-12">https://www.indiabusinessstoday.in/deals/detail/customized-cnc-brass-ball-head-bolt-wholesale-12</a>

### Customized CNC Brass Ball Head Bolt Wholesale

Product Name	Customized CNC Brass Ball Head Bolt Round Head Stud Bolt
Brand Name	Wenzhou Yuanzhi Auto parts
Model Number	YUANZH-bolt-015
Material	C70, 65Mn, Carbon Steel, Alloy Steel, Stainless Steel, Brass, or as OEM required
Grade	Class 4.6, 4.8, 5.6, 8.8, 10.9, SAE J429 Gr. 2, Gr. 5, Gr.8 or as required
Finish	Plain, Zinc Plated (Clear/Blue/Yellow/Black), black oxide, H.D.G, DAC, GOOMET, as customer need
Standard	GB, DIN, ISO, ANSI/ASTM, B7, BS, BSW, JIS etc
Size	M5-M48 , #12-3/4" or non-standard as request & design
Heat Treatment	Zn- Plated, Ni-plated, Passivated, Tin-plated, Sandblast and Anodize, Polish, Electro Painting, Black Anodize, Plain, Chrome plated, Hot Deep Galvanize (H. D. G. ) etc.
Test Equipments	Caliper, Go&No-go gauge, Tensile test machine, Hardness tester, Salt spraying tester, H.D.G thickness tester, 3D detector, Projector, Magnetic flaw detector and etc
Certification	IATF 16949 , ISO 14001, ISO19001

---

MOQ	Small order can be accepted
Loading Port	Ningbo or Shanghai
Payment term	30% deposit in advance,70% before shipment,100% TT in advance
Sample	YES
Delivery Time	Enough stock or strong production capacity ensure timely delivery
Packaging	100,200,300,500,1000PCS per bag with label,export standard carton, or according to customer special demand
Design ability	We can supply sample, OEM&ODM is welcome. Customized drawing with Decal,Frosted, Print are available as request

YUANZH Ball Head Bolt should have precise end-face pressure. By minimizing the thickness of the bushing pin head and using as long as possible a high-quality spring, it can reduce the fatigue of the spring and increase its service life.

The height of the YUANZH Ball Head Bolt of each plunger protruding from the plunger body must be uniform. Precise processing control and strict inspection procedures must ensure that the size difference between the protruding height of each plug ball head does not exceed 0.1mm. Some specifications cannot exceed 0.05mm.

Although it can be installed with a screwdriver or an Allen wrench, most experts recommend using a special spring plunger wrench especially for novices. Use of the wrong tool to run the risk of over-compressed springs and damage. As any technician knows, you should always work with the right tools. The biggest danger during installation is that the plunger spring uses too much torque. Although they are like bolts or screws, their bodies are hollow, and there is a limit to the power they can tolerate.

<https://www.yuanzhi-autoparts.com/b/stainless-steel-bolts.html>

#### **POSTED BY**

{value\_author\_name}

**Address** {value\_author\_address}

**Contact Person** {value\_primary\_contact}

**Mobile Number** {value\_author\_phone\_number}

---

**Email** {value\_author\_email}

For more details, please visit [https://www.indiabusinessstoday.in/FIXME\('route\\_'\)](https://www.indiabusinessstoday.in/FIXME('route_'))