
INTERLOCK SHAKE TILE

Price	Rs 0.00
External URL	https://www.sangobuild.com/stone-coated-roof/stone-coated-metal-roofing.html
Keywords	interlock shake tile
Hits	124
URL	https://www.indiabusinessstoday.in/products/detail/interlock-shake-tile-630

INTERLOCK SHAKE TILE

Size:1348x365mm

Effective Size:1290x315mm

Thickness:0.35-0.55mm

Coverage Area:0.41sq.m

Tiles/Sq.m:2.4 pieces

Warranty:50 years

San-gobuild Product Description

Product Name ***Interlock Shake Tile***

Material Galvalume steel(Aluminum Zinc plated steel sheet=PPGL), Natural stone chip, Acrylic resin glue

Color Black, Red, Blue, Green, Customized

Tile Size 1348x365mm

Effective Size 1290x315mm

Thickness 0.35mm,0.40mm,0.45mm,0.50mm,0.55mm

Weight 2.85-3.35kgs/pc

Coverage Area 0.41sq.m./pc

Tiles/Sq.m. 2.4pcs

Certificate SONCAP,COC,UL,ISO9001

Used Residential, Commercial construction roof

Stone Coated Roof supplier: **San-gobuild**

1.Excellent durability and waterproof

High-quality aluminum zinc plated steel sheet and natural stone chip coating with acrylic resin glue make stone coated roof tile to superior corrosion resistance and waterproof. The warranty could be last up to 50 years.

2.Lightweight and easy to install

The weight of **stone coated metal roof** tile is only 1/6 of the traditional tile, only 5.20-6.40kgs/sq.m.It is easy to transport, store and install.

3.Economic

Because Stone Coated Metal Roofing has lightweight but big size, so it usually just takes 3-5days for 2 workers to finish all the installation for a common residence and related charge of shipment and installation be reduced sharply.

4.Noise reduction and heat insulation

The stone chips could reduce the noise when raining or hailing, it also could insulate from heat when exposing to extremely UV and keep warm in Winter.

SUPPLIER

{value_author_name}

Address {value_author_address}

Contact Person {value_primary_contact}

Mobile Number {value_author_phone_number}

Email {value_author_email}

For more details, please visit [https://www.indiabusinessstoday.in/FIXME\('route_'\)](https://www.indiabusinessstoday.in/FIXME('route_'))
